

**KX-TVS50, KX-TVS95, KX-TVS125, KX-TVS225 AND KX-TVS325 FEATURES**

**Mailbox Services**  
 Greeting, After Hours  
 Greeting, Busy  
 Greeting, No answer  
 Internal message delivery  
 Mailbox name  
 Mailbox password  
 Message delivery status  
 Message reception mode  
 Message, Erase  
 Message, Fast Forward  
 Message, Pause  
 Message, Playback  
 Message, Repeat  
 Message, Rewind  
 Message, Scan  
 Message, Skip  
 New message notification  
 Play previous message  
 Private messages  
 Reply to subscriber(s)  
 Time and date stamp  
 Telephone LCD VM prompts  
 Transfer message with comments  
 Transfer message without comments

**System Administration**  
 Auto configuration (DPITS/APITS only)  
 Integration, Digital  
 Integration, In-band  
 PC-based programming  
 Quick setup  
 System manager administration  
 Utility Commands

**System Features**  
 All calls transferred to mailbox  
 Alternate extension transfer sequence  
 Auto message move/copy  
 Built-in Modem Card for Remote Access\*  
 Broadcast message  
 Call blocking  
 Call screening  
 Call transfer status  
 Call transfer to outside line\*\*\*  
 Callback number entry  
 Call ID callback\*\*\*  
 Caller ID Name Announce  
 (DPITS/APITS only)  
 Caller ID Routing (DPITS/APITS only)  
 Class of service  
 Coverage mode, Busy  
 Coverage mode, No answer  
 Covering extensions  
 Day/night service  
 Day/night/lunch service with PBX  
 (DPITS/APITS only)  
 Daylight saving time assignment  
 Department dialing  
 Dial by name  
 Direct mailbox access (DPITS/APITS only)  
 External message delivery  
 External message delivery status  
 Fax management  
 Fax transfer  
 Group distribution lists, Personal  
 Group distribution lists, System  
 Groups mailbox  
 Hold call  
 Holiday service  
 Intercom paging notification (DPITS/APITS only)  
 Live call screening (DPITS/APITS only)

**Mailbox, General Delivery**  
**Mailbox, Guest**  
**Mailbox, Interview**  
**Mailbox, Message Manager**  
**Mailbox, Subscriber**  
**Mailbox, System Manager**  
 Message waiting notification, Continuous  
 Message waiting notification, Lamp  
 Message waiting notification, Outdial  
 Message waiting notification, Pager  
 Message waiting notification, Scheduled  
 Multiple company greetings  
 Operator service, Day/Night  
 Personal Greeting for Caller ID  
 (DPITS/APITS only)  
 Prerecorded bilingual prompts  
 (English/Spanish)\*\*  
 Recordable system prompts  
 Remote call forwarding set  
 (DPITS/APITS only)  
 Remote change of company greeting  
 (DPITS/APITS only)  
 Rotary telephone service  
 Service access commands  
 Service, Automated Attendant  
 Service, Custom  
 Service, Interview  
 Subscriber Tutorial\*\*\*  
 System clock  
 System clock sync with PBX  
 (DPITS/APITS only)  
 System prompts after personal greeting  
 System reports  
 Two-way record (DPITS/APITS only)  
 Two-way transfer (DPITS/APITS only)  
 Trunk group based routing

\* Available in KX-TVS325 only

\*\* Spanish prompts not available in KX-TVS50

\*\*\* Available only in the KX-TVS95, 125, 225, & 325

VOICE PROCESSING SPECIFICATIONS CHART 1							
Model	APITS Ports	DPITS Ports	In-Band Ports	Bilingual Voice Prompts	Storage (Hours)	Mailboxes	Messages per Mailbox
KX-TVS50	2	2	2	No	2 Expandable to 4	32	100
KX-TVS95	2	2	2	Eng/Span	6	64	100
KX-TVS125	-	6	4	Eng/Span	32	64	100
KX-TVS225	-	12	6	Eng/Span	64	1024	100
KX-TVS325	-	24	12	Eng/Span	128	1024	100

VOICE PROCESSING PORT CONFIGURATION CHART 2		
System	Expansion Cards Required	Type of Integration Supported
KX-TVS50	Configured with 2 Ports - Not Expandable	DPITS/APITS/Inband
KX-TVS95	Configured with 2 Ports - Not Expandable	DPITS/APITS/Inband
KX-TVS125	Initially configured with 1 KX-TVS204 4 port card. Expandable to 6 Ports DPITS with the addition of 1 KX-TVS102 card. With the initial KX-TVS204 card removed, up to 2 KX-TVS102 cards can be installed for 4 ports Inband.	DPITS/Inband
KX-TVS225	Initially configured with 1 KX-TVS204 4 port card. Expandable to 12 Ports DPITS with the addition of 2 KX-TVS204 cards. With the initial KX-TVS204 card removed, up to 3 KX-TVS102 cards can be installed for 6 ports Inband.	DPITS/Inband
KX-TVS325	Initially configured with 1 KX-TVS204 4 port card. Expandable to 24 Ports DPITS with the addition of 5 KX-TVS204 cards. With the initial KX-TVS204 card removed, up to 6 KX-TVS102 cards can be installed for 12 ports Inband.	DPITS/Inband

KX-TDA 50/100/200 SYSTEM SPECIFICATIONS	
Switching:	Non Blocking Distributed Time Switch
Power Source:	AC120v 60Hz
Wiring:	SLT: One Pair (T,R) DPT: One Pair (D1,D2) Or 2 Pair (T,R,D1,D2) APT: 2 Pair (T,R,D1,D2) DSS: One Pair (D1,D2)
Certification No:	TDA100/200 ACJMF03AKX-TDA100 TDA50 ACJMF03AKX-TDA50
Ringer Equivalence No:	0.3A
Facility Interface Code:	02LS2, 04DU9,BNDN/1KN/1SN, METALLIC
Service Order Code:	9.0F, 6.0P
Dimensions:	KX-TDA50 .....(10-3/4 In x 14-3/4 In x 4-5/8 In) KX-TDA100 .....(13-1/3 In x 15-3/5 In x 10-4/5 In) KX-TDA200 .....(17-1/5 In x 16-3/5 In x 10-4/5 In)
Operating Environment	
Temperature	0 °C to 40 °C (32 °F to 104 °F)
Humidity	10 % to 90 % (non condensing)
Consumption	KX-TDA50 with Main PS .....(at 120 V AC, 60 Hz) KX-TDA50 with Main + Optional PS .....(at 120 V AC, 60 Hz) KX-TDA100 with PSU-M .....210 W, 2.2 A (at 120 V AC, 60 Hz) KX-TDA200 with PSU-M .....240 W, 2.5 A (at 120 V AC, 60 Hz) KX-TDA200 with PSU-L .....490 W, 5.1 A (at 120 V AC, 60 Hz)

Units, Weights and Specifications subject to change.